

Unit # GP120559
 Model RS120
 Capacity 120,000 LBS @24 IN L.C.
 Power LP
 Tires SOLID PNEUMATIC
 Lift Height 10FT
 Free Lift 0
 Attachment
 Boom/Stand/Pin Yes: Boom Hgt 9'-11" Boom Retracted 6 FT 10 IN Boom Extend 9 FT 6 IN Boom Up 23 FT 3 IN 7,500LBS
 Weight TRK WT 66,200 LBS
 Width 8FT- 6 IN
 Length 18 FT- 3IN ADD 8 FT FORKS 26FT-3 IN OAL
 Height 9FT-11 IN
 Forks 8 FT 5X12X96
 Counterweights 4 WTS @8,000L EACH
 Permitted: Y
 Loads For Trucking: 2 TRK 1 LOAD CTR WTS AND BOOM 2nd LOAD

Brute Lift		BT120-24				
Heavy Lifting Equipment		Load Chart				
L/C	base unit	base + 1	base + 2	base + 3	base + 4	
24"	60,000 lb	75,000 lb	90,000 lb	105,000 lb	120,000 lb	
36"	50,000 lb	62,500 lb	75,000 lb	87,500 lb	100,000 lb	
48"	42,857 lb	53,571 lb	64,285 lb	75,000 lb	85,714 lb	
60"	37,500 lb	46,875 lb	56,520 lb	65,625 lb	75,000 lb	
72"	33,333 lb	41,667 lb	50,000 lb	58,333 lb	66,666 lb	
84"	30,000 lb	37,500 lb	45,000 lb	52,500 lb	60,000 lb	
96"	27,273 lb	34,091 lb	40,909 lb	47,727 lb	54,545 lb	

Base unit is lift truck with supplied forks installed and no removable counterweight
 Base + 1 is base unit plus 1 supplied removable counterweight
 Base + 2 is base unit plus 2 supplied removable counterweight
 Base + 3 is base unit plus 3 supplied removable counterweight
 Base + 4 is base unit plus 4 supplied removable counterweight



UNIT W/O CTRSWTS AND BOOM